PATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY REPORT ON PATENTABREG TY 5 JUL 2005 (Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

	_	•	JOL	2003
WIPO	_	_		PCT
	_			ru:

Applicant's or agent's file reference FOR FURTHER ACTION See Form PCT/IPEA/416 P6510PC00

International application I	No. International filing da	ate (day/month/year)	Priority date (day/month/year)
PCT/AU2004/001061	10 August 2004		11 August 2003
International Patent Class	ification (IPC) or national classification	and IPC	
Int. Cl. ⁷ E02D 35/00	·		
Applicant .			
ONG, Chin,Chai			
	national preliminary examination report, e 35 and transmitted to the applicant acc		national Preliminary Examining
2. This REPORT consist	s of a total of 3 sheets, including this	cover sheet.	
3. This report is also acco	ompanied by ANNEXES, comprising:	9	
a. X (sent to the ap	pplicant and to the International Bureau,	a total of 10 sheets, a	s follows:
x sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions).			
sheets which supersede earlier sheets, but which this Authority considers contain an amendment that goes beyond the disclosure in the international application as filed, as indicated in item 4 of Box No. I and the Supplemental Box.			
b. (sent to the International Bureau only) a total of (indicate type and number of electronic carrier(s)), containing a sequence listing and/or table related thereto, in computer readable form only, as indicated in the Supplemental Box Relating to Sequence Listing (see Section 802 of the Administrative Instructions).			
4. This report contains i	ndications relating to the following item	s:	
X Box No. I	Basis of the report		. •
Box No. II	Priority		
Box No. III	Box No. III Non-establishment of opinion with regard to novelty, inventive step and industrial applicability		
Box No. IV	Lack of unity of invention		
X Box No. V	Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement		
Box No. VI	Certain documents cited		
Box No. VII	Box No. VII Certain defects in the international application		
Box No. VIII	Box No. VIII Certain observations on the international application		
Date of submission of the	demand .	Date of completion of	the report
4 March 2005		17 June 2005	• ***
Name and mailing address o	f the IPEA/AU	Authorized Officer	
AUSTRALIAN PATENT OFFICE			

Date of submission of the demand .	Date of completion of the report	
4 March 2005	17 June 2005	
Name and mailing address of the IPEA/AU	Authorized Officer	
AUSTRALIAN PATENT OFFICE PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaustralia.gov.au	E.J. MARTYN	
Facsimile No. (02) 6285 3929	Telephone No. (02) 6283 2332	



International application No.

PCT/AU2004/001061

Box	No. 1			
1.	With other	regard to the language, this report is based on the international application in the language in which it was filed, unless rwise indicated under this item.		
		This report is based on translations from the original language into the following language, which is the language of a translation furnished for the purposes of:		
		international search (under Rules 12.3 and 23.1 (b))		
	publication of the international application (under Rule 12.4)			
		international preliminary examination (under Rules 55.2 and/or 55.3)		
2.	2. With regard to the elements of the international application, this report is based on (replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report):			
		the international application as originally filed/furnished		
	X	the description:		
		pages $1-5, 8-14$ as originally filed/furnished		
		pages* 6, 7 received by this Authority on 10 June 2005 with the letter of 10 June 2005 pages* received by this Authority on with the letter of		
	X	the claims:		
		pages as originally filed/furnished		
		pages* as amended (together with any statement) under Article 19		
	(GE)	pages* 15 - 21 received by this Authority on 10June 2005 with the letter of 10 June 2005 pages* received by this Authority on with the letter of		
	X	the drawings:		
		pages 1 - 7 as originally filed/furnished pages* received by this Authority on with the letter of		
		pages* received by this Authority on with the letter of		
3		a sequence listing and/or any related table(s) - see Supplemental Box Relating to Sequence Listing. The amendments have resulted in the cancellation of:		
٦.		<u> </u>		
		the description, pages		
		the claims, Nos.		
		the drawings, sheets/figs		
		the sequence listing (specify):		
		any table(s) related to the sequence listing (specify):		
4.		This report has been established as if (some of) the amendments annexed to this report and listed below had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).		
		the description, pages		
		the claims, Nos.		
		the drawings, sheets/figs		
		the sequence listing (specify):		
		any table(s) related to the sequence listing (specify):		
*	If it	tem 4 applies, some or all of those sheets may be marked "superseded."		

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/AU2004/001061

Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

	Statement
ĸ.	Statement
ı.	DIGITALITY

		•
Novelty (N)	Claims 1 - 19	YES
	Claims	NO
Inventive step (IS)	Claims 1 - 19	YES
	Claims	NO
Industrial applicability (IA)	Claims 1 - 19	YES
	Claims .	NO

2. Citations and explanations (Rule 70.7)

Claims 1 – 19

The invention of the amended claims is an underpinning pile system comprising a pile transfer beam, a pile anchor head to engage with the head of the pile and a jacking means. The transfer beam includes an opening to receive the pile anchor head, which in turn receives the pile. The transfer beam is arranged to engage under the foundations at points on either side of the opening. The jacking means engages between the transfer beam and the pile to drive the pile downwardly through the transfer beam through the pile anchor head.

No individual citation or obvious combination of citations discloses the present invention.

The closest art:

CA 2235890 A

US 5433556 A

US 6193442 B

US 2001/0046415 A ·

Therefore the subject matter of these claims is new and not obvious and meets the requirements of Article 33(2) and 33(3) PCT with regard to novelty and inventive step.

A significant aspect of the present invention is that the pile anchor head is adapted to receive the building load and transfer it to practically any kind of material and shape of pile without restricting to the common use of steel pipes in underpinning.

According to one aspect of the present invention there is provided an underpinning pile system for lifting and underpinning a settling foundation comprising:

- 10 a pile;
 - a transfer beam having an opening for receiving the upper end of the pile, the transfer beam being arranged to engage with the foundation on at least two points, one either side of said opening;
- 15 a pile anchor head receivable in the opening in the transfer beam, the pile anchor head having a hollow section for receiving the upper end of the pile and a portion arranged to engage with the transfer beam adjacent the opening; and a jacking means engageable with the transfer beam and the upper end of the pile;
 - wherein the jacking means exerts a force on the upper end of the pile to drive the pile downwardly relative to the stationary transfer beam.
- In another aspect of the present invention, there is provided a method for installing an underpinning pile system for lifting and underpinning a settling foundation characterised by comprising the steps of: excavating a hole adjacent to the foundation;
- placing a transfer beam having an opening for receiving the upper end of a pile in the excavated hole, the transfer beam being arranged to engage with the foundation on at least two

points, one either side of said opening;

placing a pile anchor head having a hollow section for receiving the upper end of the pile in the opening in the transfer beam such that the pile anchor head engages with the transfer beam adjacent the opening;

5 placing a pile through the hollow section in the pile anchor head;

engaging a jacking means with the transfer beam and the upper end of the pile; and

10

15

25

30

.

driving the pile downwardly relative to the stationary transfer beam by operation of the jacking means.

BRIEF DESCRIPTION OF THE DRAWINGS

Further understanding of the aspects of the present invention and their advantages will be discerned after studying the Detailed Description in conjunction with the accompanying drawings in which:-

Fig 1 shows an underpinning pile according to one embodiment of the present invention;

Fig 2 shows an underpinning piling system and the auxiliary 20 apparatus;

Fig 3a shows a typical pile anchor head with optional attachments of triangular wedges and with nuts and bolts at corresponding positions to match a transfer beam;

Fig 3b shows another variation of a typical pile anchor head with a wider out splayed flange and web;

Fig 4 shows installing two C-channels sides by side on each side of the pile anchor head;

Fig 5 shows the placing of a thrust block into the space between the gap of the parallel C-channels and inserting two large pins into the receiving holes at the ends of the thrust block just clearing beneath the soffit of the parallel C-channels;

Fig 6 shows the placing of a hydraulic jack over the top of the underpinning pile;

CLAIMS

- 1. An underpinning pile system for lifting and underpinning a settling foundation characterised by comprising:
- a pile;

5

10

20

- a transfer beam having an opening for receiving the upper end of the pile, the transfer beam being arranged to engage with the foundation on at least two points, one either side of said opening;
- a pile anchor head receivable in the opening in the transfer beam, the pile anchor head having a hollow section for receiving the upper end of the pile and a portion arranged to engage with the transfer beam
- 15 adjacent the opening; and
 - a jacking means engageable with the transfer beam and the upper end of the pile;
 - wherein the jacking means exerts a force on the upper end of the pile to drive the pile downwardly relative to the stationary transfer beam.
 - An underpinning pile system in accordance with claim
 characterised in that the pile anchor head includes a
 - locking means for securing movement of the pile relative
- to the pile anchor head once the pile is driven into
- 25 position under a jacking load.

- 3. An underpinning pile in accordance with claim 2, characterised in that the locking means comprises an anchor plate securable across the hollow section to bear on top of the pile.
- 5 4. An underpinning pile in accordance with claim 3 characterised in that the pile anchor head comprises a hollow member having a tabular cross section complementary to the cross sectional shape of the pile.
- 5. An underpinning pile in accordance with claim 3,

 10 characterised in that the cross section of the hollow

 member is complementary to the shape of the anchor plate

 such that the anchor plate is secured within the hollow

 member against the upper end of the pile by welding to

 inner surfaces of the hollow member.
- 15 6. An underpinning pile in accordance with any one of the preceding claims, characterised in that the portion of the pile anchor head that engages with the transfer beam comprises a plurality of flanges that engage with an underside of the transfer beam.
- 7. An underpinning pile in accordance with any one of the preceding claims characterised in that the transfer beam comprises two members secured parallel to and separated from each other to define the opening.

- 8. An underpinning pile in accordance with claim 7, characterised in that the members each comprise a C-channel members arranged with open sides thereof oriented in opposite directions.
- 9. An underpinning pile in accordance with any one of the preceding claims, characterised in that the jacking means comprises an inverted U-shaped thrust block and a jack, the inverted U-shaped thrust block arranged such that ends of parallel legs of the thrust block extend
- downwardly through the opening in the transfer beam on either side of the pile and engage with the transfer beam, and the jack engages between the upper horizontal member of the inverted U-shaped thrust block and the upper end of the pile to force the pile downwardly relative to the thrust block.
 - 10. An underpinning pile in accordance with claim 9, characterised in that the ends of the legs of the inverted U-shaped thrust block are provided with holes to receive locking pins such that when the holes are
- positioned below the transfer beam and the locking pins are inserted through the holes, the locking pins engage with the lower surface of the transfer beam to resist upward movement of the U-shaped thrust block relative to the transfer beam.

- 11. An underpinning pile in accordance with claim 10, characterised in that the legs of the U-shaped thrust block include outwardly extending wedges, the wedges engaging with an upper surface of the transfer beam when the U-shaped thrust block is inserted downwardly through the opening in the transfer beam.
- 12. A method for installing an underpinning pile system for lifting underpinning a and settling foundation characterised by comprising the steps of:
- 10 excavating a hole adjacent to the foundation; placing a transfer beam having an opening for receiving the upper end of a pile in the excavated hole, the transfer beam being arranged to engage with the foundation on at least two points, one either side of 15
 - placing a pile anchor head having a hollow section for receiving the upper end of the pile in the opening in the transfer beam such that the pile anchor head engages with the transfer beam adjacent the opening;
- 20 placing a pile through the hollow section in the pile anchor head;
 - engaging a jacking means with the transfer beam and the upper end of the pile; and
 - driving the pile downwardly relative to the stationary
- 25 transfer beam by operation of the jacking means.

said opening;

5

- 13. A method for installing an underpinning pile system in accordance with claim 12, characterised by including the step of securing any further movement of the pile relative to the pile anchor head once the pile is driven into position and loaded with a locking means to engage the pile with the pile anchor head.
- 14. A method for installing an underpinning pile system in accordance with claim 13, characterised by including the steps of driving the pile downwardly until the upper end of the pile is within the hollow section of the pile anchor head and inserting an anchor plate into the hollow section to bear on the top of the pile and welding the anchor plate to internal surfaces of the hollow section of the pile anchor head.
- 15. A method for installing an underpinning pile system in accordance with any one of claims 12 to 14, characterised in that engaging the jacking means with the transfer beam and the pile comprises the steps of:
- inserting legs of an inverted U-shaped thrust block

 downwardly through the opening in the transfer beam such that the legs are positioned on opposite sides of the pile;
 - engaging ends of the legs with the transfer beam; and

5

10

inserting a jack between the upper end of the pile and a lower side of a horizontal member of the inverted U-shaped thrust block.

- 16 A method for installing an underpinning pile system in

 5 accordance with claim 15, characterised in that locking
 pins are inserted through holes provided in the ends of
 the legs of the inverted U-shaped thrust block when the
 ends of the legs are located below the transfer beam,
 such that the locking pins engage with a lower surface of
 the transfer beam and thereby resist upward movement of
 the inverted U-shaped thrust block relative to the
 transfer beam.
- 17. A method for installing an underpinning pile system in accordance with claim 16 characterised in that the

 15 step of driving the pile downwardly relative to the transfer beam comprises the step of extending the jack to force the pile downwardly relative to the thrust block.

 18. A method for installing an underpinning pile system in accordance with any one of the preceding claims including the step of securing the pile anchor head to the transfer beam once the pile is driven into position and secured to the pile anchor head.
- 19. A method for installing an underpinning pile system in accordance with claim 19 characterised by placing a plurality of wedges such that the wedges engage against

the pile anchor head and the transfer beam, and welding the wedges to the transfer beam and the pile anchor head.